Amendments To The Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

What is claimed is:

- 1. (Currently Amended) A hand-held device (1;101) having a housing (3;103), a track (17;117) in the housing, a chain (19;119) of capsules (21;121) in the track and a conveying mechanism (27,31b-f; 131,139) adapted to convey the chain along the track.
- 2. (Currently Amended) The device of claim 1, wherein the conveying mechanism has a manually-operable actuator element (29a;139) for actuating the conveying mechanism.
- 3. (Currently Amended) The device of claim 2, wherein the actuator element is rotatably mounted to the housing, rotation thereof actuating the conveying mechanism.
- 4. (Currently Amended) The device of <u>claim 1</u> any-one of the preceding claims, wherein the conveying mechanism has a sprocket (31b-f;131) rotatably mounted in the housing and positioned to engage the capsule chain for advancement thereof in the track.
- 5. (Currently Amended) The device of claim 1 4 when appended to claim 2 or 3, wherein the conveying mechanism has a manually-operable actuator element for actuating the conveying mechanism wherein the sprocket is operatively coupled to the actuator element.
- 6. (Original) The device of claim 5, wherein the conveying mechanism consists of the sprocket and the actuator element.

- 7. (Currently Amended) The device of claim 4, 5 or 6, wherein the track has a bend (35b-f;135f) and the sprocket is located at the bend.
- 8. (Currently Amended) The device of claim 4, wherein the sprocket is one of a plurality of sprockets (35b-f) of the conveying mechanism, each rotatably mounted in the housing and positioned to engage the capsule chain for advancement thereof in the track.
- 9. (Currently Amended) The device of claim 8, wherein the track has a plurality of bends (35b-f) and each sprocket is located at a different bend.
- 10. (Original) The device of claim 9, wherein there is a sprocket for each bend in the track.
- 11. (Currently Amended) The device of claim 7, 9 or 10, wherein the or each sprocket is located on the inside of the associated track bend.
- 12. (Currently Amended) The device of claim 2 or any claim appendent thereon, wherein the conveying mechanism has a drive mechanism (29a-f) adapted to impart drive to the capsule chain in response to operation of the actuator element.
- 13. (Currently Amended) The device of claim 12, wherein the drive mechanism has a drive wheel train (27).
- 14. (Currently Amended) The device of claim 13 when appended to claim 8, wherein the conveying mechanism has a sprocket rotatably mounted in the housing and positioned to engage the capsule chain for advancement thereof in the track, wherein the sprocket is one of a plurality of sprockets of the conveying mechanism, each rotatably mounted in the housing and positioned to engage the capsule chain for advancement thereof in the track, and wherein the drive wheel train has a plurality of wheels (29b-f) rotatably mounted in the

housing, each wheel operatively coupled to a different sprocket whereby rotation of the wheels causes rotation of the associated sprockets.

- 15. (Original) The device of claim 14, wherein each sprocket is mounted on the associated wheel for rotation therewith.
- 16. (Original) The device of claim 15, wherein the sprocket and wheel of each associated pair are co-axially mounted in the housing.
- 17. (Currently Amended) The device of claim 16, wherein each sprocket has a spindle (33b f), each spindle being mounted on the associated wheel at its axis of rotation.
- 18. (Currently Amended) The device of any one of claims 13 to 17, wherein at least one predetermined wheel (29b) of the drive wheel train is in engagement with the actuator element which is manually movable by a user of the device and wherein movement of the actuator element causes rotation of the at least one predetermined wheel to drive the drive wheel train.
- 19. (Currently Amended) The device of any one of claims 13 to 18, wherein the drive wheel train is a drive gear wheel train with the wheels being gear wheels.
- 20. (Original) The device of claim 19, wherein the gear wheels are spur gear wheels.
- 21. (Currently Amended) The device of <u>claim 1</u> any one of the proceding claims, wherein the capsules in the chain have elongate bodies (26) and are arranged upright in the track in side-by-side relation.
- 22. (Original) The device of claim 21, wherein the capsules are generally cylindrical.

- 23. (Currently Amended) The device of <u>claim 1</u> any one of the preceding claims in which the capsules contain a powder product.
- 24. (Currently Amended) The device of <u>claim 1</u> any one of the <u>preceding</u> claims, wherein the capsules contain a medicament.
- 25. (Currently Amended) The device of claims 23 and 24, wherein the capsules each contain a unit dose of a medicament powder.
- 26. (Currently Amended) The device of <u>claim 1</u> any one of the preceding claims in which the capsules are linked together.
- 27. (Currently Amended) The device of <u>claim 1</u> any one of the preceding claims in which the track is endless.
- 28. (Original) The device of claim 27 in which the chain is endless.
- 29. (Currently Amended) The device of <u>claim 1</u> any one of the preceding claims in which the track has at least one fold section (23;123) to provide the track with a space-saving configuration.
- 30. (Currently Amended) The device of claim 29 when appended directly or indirectly on claim 7, wherein the track has a bend and the sprocket is located at the bend and wherein the bend is at the inside of the fold section.
- 31. (Currently Amended) The device of <u>claim 1</u> any one of the preceding claims adapted for use as a component part of an inhalation device for delivering medicament to a patient.
- 32. (Currently Amended) An inhalation device for delivering medicament to a patient incorporating the hand-held device of <u>claim 1</u> any one of the <u>preceding claims</u>.

33. (Canceled).